



HS/600SC



Art Code	Misure esterne mm. External dim. mm.			Misure interne mm. Internal dim. mm.			Dim. porta mm. Door dim. mm.		Numero catenacci Number of bolts		Peso Weight	Litri Volume
	Alt/H	Larg/W	Prof/D	Alt/H	Larg/W	Prof/D	Alt/H	Larg/W	Oriz/Horiz	Vert	Kg	Lt
HS/400S	1560	365	320	1300*	360	265	1410	280	3	1+1	50	148
HS/400SC	1560	365	320	1300*	360	265	1410	280	3	1+1	54	148
HS/600SC	1560	535	320	1300*	530	265	1410	430	3	1+1	70	218

* Esclusa l'altezza del ripiano (HS/400S) o della cassetta interna (HS/400SC - HS/600SC).

* Excluding the high of the shelf (HS/400S) or the security box (HS/400SC - HS/600SC).


🇮🇹 Chiave a Doppia Mappa

- Struttura monoblocco in lamiera d'acciaio dello spessore di 2 mm.
- Spessore totale del battente 50 mm.
- Serratura di sicurezza a 6 leve con chiave a doppia mappa (2 chiavi in dotazione).
- Estrazione della chiave impossibile a catenacci rientrati.
- 5 catenacci in acciaio nichelato Ø 22 mm.
- Completo di supporto e base per fucili in legno massello verniciato.
- Fori di ancoraggio sulla base e sullo schienale (4+4).
- Verniciatura a polvere termoindurente con essiccazione a forno.

HS/400S: • con ripiano - 7 fucili

HS/400SC: • con tesoretto - 7 fucili

HS/600SC: • con tesoretto - 11 fucili



Particolare del ripiano del mod. HS/400S


🇬🇧 Double-Bitted Key

- One-piece steel construction with a body's thickness of 2 mm.
- Total thickness (with lock panel): 50 mm.
- Security lock with 6 levers and double-bitted key (2 keys supplied).
- Key-retaining lock in open position.
- 5 nickel-plated steel bolts Ø 22 mm.
- Painted solid wood rifles rack and base.
- Pre-drilled anchor holes on floor and wall mounting (4+4).
- Oven dried thermo-hardening powder painting.

HS/400S • with sec. box - 7 rifles

HS/400SC • with sec. box - 7 rifles

HS/600SC • with sec. box - 11 rifles



Particular of shelf of mod. HS/400S